



Centreo

THE RANGE OF CENTRAL MOTORS FROM SOMFY

Quality that's central to your requirements!



HOME MOTION by
somfy[®]

CENTREO

Because a high-quality opening is an essential requirement



*Durable
Quality
Personal safety
Easy installation
5-year guarantee*

Proven reliability

Centreo offers the ultimate in reliability, built with **robust materials, proven technology, a solid and durable fastening system, patented on high level of torques.**

PROOF:

The new range of central motors from Somfy have withstood the most rigorous endurance tests, equivalent to approximately **10 years of use.**

Long-lasting performance

The curtain is operated smoothly, lasting just as long as the motor.
The motor maintains its nominal torque throughout the operating cycle.
With Centreo, Somfy guarantees a long-term investment.

100% compliant with safety standards

Personal safety is of paramount importance. The integrated brake is able to **hold up to 1.2 times** the nominal torque, ensuring that the shutter is safe every time it stops (EN 60335-2-103).

In addition, the moving parts of the **motor and electrical cables are entirely inaccessible** (EN 60335-1 §23-6, § 25-23).

Easy to move manually the curtain

Centreo is equipped with a built-in declutching system that **directly takes action on the gearbox which allows an effortless manual opening in case of power failure.**



Declutch handle kit 9013927

Quick and easy to install

Centreo offers **quick and simple installation.** It features a new fastening system, which has been specially developed to make the installation process easier, **and memory rings to set end-of-travel points.**



★ Compatible with all the range of Somfy controls

Axroll Plus 1841033	Keygo RTS 1841064	Universal key switch 1805116	Security box 9011411	Dry contact receiver 1841102

★ Adaptors

Kit Adaptation MC Ø60/34 9015363	Kit Adaptation MC Ø60/42 9015364	Kit Adaptation MC Ø60/48 9015366	
--	--	--	--

★ A wide range of compact motors

Centreo's compact design means that it can be used to motorise narrow curtains.

With a wide range of Centreo motors available, you will be able to find the right motor, whatever the size of your opening.

	Reference	For curtains up to	Wheel Ø mm	Tube Ø mm	Brake and declutching	Power W	Speed rpm	Current A	End-of-travel capacity	Weight kg	Length mm		
											La	Lb	
Centreo 1	1207028	160 kg ⁽¹⁾	200	60 ⁽²⁾	With	280	10	1.25	12 rpm	6.5 ⁽³⁾	342	-	
Centreo 1	1207029	160 kg ⁽¹⁾	200	60 ⁽²⁾	Without	280	10	1.25	12 rpm	6.5 ⁽³⁾	342	-	
Centreo 1	1207030	150 kg ⁽¹⁾	220	60 ⁽²⁾	With	280	10	1.25	12 rpm	6.5 ⁽³⁾	342	-	
Centreo 1	1207031	150 kg ⁽¹⁾	220	60 ⁽²⁾	Without	280	10	1.5	12 rpm	6.5 ⁽³⁾	342	-	
Centreo 2	1207032	200 kg ⁽¹⁾	200	60 ⁽²⁾	With	340	10	1.5	12 rpm	6.8 ⁽³⁾	357	342	
Centreo 2	1207033	200 kg ⁽¹⁾	200	60 ⁽²⁾	Without	340	10	1.5	12 rpm	6.8 ⁽³⁾	357	342	
Centreo 2	1207034	200 kg ⁽¹⁾	220	60 ⁽²⁾	With	340	10	1.5	12 rpm	6.8 ⁽³⁾	357	342	
Centreo 2	1207035	200 kg ⁽¹⁾	220	60 ⁽²⁾	Without	340	10	1.5	12 rpm	6.8 ⁽³⁾	357	342	
Centreo 2	1207036	200 kg ⁽¹⁾	220	76	With	340	10	1.5	12 rpm	6.8 ⁽³⁾	357	342	
Centreo 2	1207037	200 kg ⁽¹⁾	220	76	Without	390	10	1.7	12 rpm	6.8 ⁽³⁾	357	342	
Centreo 3	1207040	255 kg ⁽¹⁾	220	60 ⁽²⁾	With	500	10	2.2	12 rpm	7 ⁽³⁾	372	357	
Centreo 3	1207041	255 kg ⁽¹⁾	220	60 ⁽²⁾	Without	500	10	2.2	12 rpm	7 ⁽³⁾	372	357	
Centreo 3	1207042	255 kg ⁽¹⁾	220	76	With	500	10	2.2	12 rpm	7 ⁽³⁾	372	357	
Centreo 3	1207048	230 kg ⁽¹⁾	240	76	With	500	10	2.2	12 rpm	7 ⁽³⁾	372	357	
Centreo 4	1207043	350 kg ⁽¹⁾	220	60 ⁽²⁾	With	800	10	3.5	12 rpm	10.5 ⁽³⁾	342	342	
Centreo 4	1207045	350 kg ⁽¹⁾	220	76	With	800	10	3.5	12 rpm	10.5 ⁽³⁾	342	342	
Centreo 4	1207046	350 kg ⁽¹⁾	240	76	With	800	10	3.5	12 rpm	10.5 ⁽³⁾	342	342	
SASO	Centreo 2 SASO	1207038	180 kg ⁽¹⁾	220	60 ⁽²⁾	With	390	12	1.7	12 rpm	6.8 ⁽³⁾	357	342
	Centreo 2 SASO	1207049	180 kg ⁽¹⁾	220	76	With	390	12	1.7	12 rpm	6.8 ⁽³⁾	357	342
	Centreo 4 SASO	1207044	300 kg ⁽¹⁾	220	60 ⁽²⁾	With	800	12	3.5	12 rpm	10.5 ⁽³⁾	342	342
	Centreo 4 SASO	1207047	300 kg ⁽¹⁾	240	76	With	800	12	3.5	12 rpm	10.5 ⁽³⁾	342	342

⁽¹⁾ for a perfectly-balanced curtain, with a wheel Ø of 220 mm

⁽²⁾ motor can be adapted for tube Ø of 34, 42 and 48 mm, using an adaptor kit

⁽³⁾ weight of motor with a wheel Ø of 220 mm

